

对比表：解码

	型号	Director Mk2	Elector	Diamond	Phonitor x
线路输入	XLR (平衡)	● (2 × 立体声)	● (3 × 立体声)	○	●
	RCA (平衡)	● (4 × 立体声)	● (3 × 立体声)	○	○
线路输出	XLR (平衡)	●	●	●	●
	RCA (平衡)	●	●	●	●
磁带监听	发送 / 返回	●	●	○	○
点阵显示	信号源和采样率	●	○	●	
VU 表	ø36 毫米, 带发光 VU	●	●		●
	0 dBVU 校准 (+4dBu)	0 / 6 / 12 dB	0 / 6 / 12 dB	○	0 / 10 dB
数模转换器	型号	DAC768v2	○	DAC768v2	DAC768xs (可选)
	SLP120 (超低通滤波器)	●	○	●	○
	比特 / 最大 SR kHz	32 / 768	○	32 / 768	32 / 768
	DSD (最大)		○		
	USB (USB-B)	●	○	●	●
	AES (S/P-DIF 专业; XLR)	●	○	●	○
	同轴 (S/PDIF,RCA)	●	○	●	●
	光纤 (S/PDIF,Toslink)	●	○	●	●
	字钟	○	○	●	○
参数 (模拟 / 数字)	动态范围	135 dB	135 dB	134.5 dB (0 dBFS=+15 dBu → 117dB)	135 dB
	频率范围	10 Hz — 100 kHz	10 Hz — 100 kHz	10 Hz — 100 kHz	10 Hz — 100 kHz
	串音	-103 dBu	-112 dBu	-108 dBu	-112 dBu
	THD+N	0.000992%	0.000992%	0.000992%	0.00085%
远程控制	信号源选择	●	○	○	○
	音量	●	●	○	●
尺寸及重量	宽 × 高 × 深 (包括支脚)	278 × 100 × 300mm 11" × 4" × 11.81"	278 × 100 × 300mm 11" × 4" × 11.81"	278 × 57 × 300mm 11" × 2.25" × 11.81"	278 × 100 × 300mm 11" × 4" × 11.81"
	重量	4.55kg / 10 lbs	4.25kg / 9.37 lbs	3.15kg / 6.95 lbs	4.4kg / 9.7 lbs