


Active 10" Studio Subwoofer




Packaging



Cardboard box dimensions (HxWxD):
620 x 485 x 575 mm / 24.41" x 19.10" x 22.64"
Total weight:
26 kg / 57.32 lb.

Frequency Response



Specification Chart

Dimensions (WxHxD)	330 x 485 x 430 mm	Phase inversion	0°/180°	XLR in right	impedance 10kΩ
Dimensions (WxHxD)	12.99" x 19.09" x 16.93"	Switchable satellite filter	flat/80Hz	XLR in LFE	impedance 10kΩ
Free-field freq. range (-3dB)	24Hz - 300Hz	Variable subwoofer filter	60-140Hz + LFE	XLR out satellite left	impedance 10kΩ
Woofer	250mm/10"	LED brightness setting		XLR out satellite right	impedance 10kΩ
Maximum SPL @ 1m	108dB	Level lock dip switch		XLR out (LFE)	impedance 10kΩ
Number of amplifiers	1	Filter lock dip switch		Power consumption	
Output power	400W	Input level dip switch	+7dBu/+22dBu	Standby	< 1W
Protection	Limiter	Auto-standby dip switch		Full output	410W
User settings		Connectors		Misc.	
System volume (Satellites & Sub)	-inf. - +6dB	RCA in (mono)	impedance 10kΩ	IR remote control	
Subwoofer volume	-inf. - +6dB	XLR in left	impedance 10kΩ	Weight	19.6 kg / 43.2 lb

Physical Data

