WIRELESS ME GREAT AUDIO EVERY TIME

Record professional sound for your videos with the Wireless ME™ microphone system. Simply clip it onto your talent to be recording crystal-clear wireless audio in seconds. Works with cameras, computers and smartphones, and is compatible with all social media apps, including Instagram and TikTok. Also compatible with free RØDE video and audio apps, including the RØDE Capture iOS camera app for dual-camera video recording. Features microphones built into both the transmitters and receiver for recording everything from two-way interviews to reaction videos, with GainAssist technology ensuring your audio is perfect every time.

- Simple to use
- Dual-channel system with two transmitters and one receiver
- GainAssist technology for crystal-clear audio
- Built-in microphones no additional accessories required
- Works with cameras, computers and smartphones (iOS and Android)
- Compatible with free RØDE video and audio apps





ACOUSTIC & ELECTRICAL SPECIFICATIONS

Acoustic Principle:	Pre-polarised pressure transducer
Polar Pattern:	Omnidirectional
Frequency Range::	20 Hz – 20 kHz
Dynamic Range:	100dB
Max SPL:	122dB SPL
Equivalent Noise (dBA):	22dBA
Analog Inputs:	TRS (lavalier microphone Input)
Output Connection:	3.5mm TRS USB-C
Computer Connectivity:	USB-C
Bit Depth:	24-bit
Sample Rate:	48 kHz
Minimum Operating Systems Requirements:	macOS 10.15 above Windows 10 and above iOS 14 Android 11
Power Requirements:	In-built rechargeable lithium-ion battery charged via 5V USB
Operating Time:	7 hours
Transmission Range:	>100m (line of sight)







WORKS WITH CAMERAS & SMARTPHONES



MECHANICAL SPECIFICATIONS

WHAT'S IN THE BOX

Weight (grams):	TX 32
	RX 32
Dimensions (millimetres):	TX: 44mm x 45.3mm x 18.3mm
	RX: 44mm x 45.3mm x 18.3mm
Included Accessories:	2 x Transmitters
	1 x Receiver
	1 x SC21 USB-C to Lightning Cable
	2 x SC22 USB-C to USB-C Cable
	1 x SC2 3.5mm TRS to TRS cable
	1 x SC7 3.5mm TRRS to TRS cable
	3 x Fur windshield
	1 x Carry Pouch
RØDE Software Compatibility:	RØDE Central
	RØDE Connect
	RØDE Reporter
	RØDE Capture








DIMENSIONS

45.3mm

POLAR PATTERN



FREQUENCY RESPONSE

